

Stress Function $\phi(x, y)$


$$\left\{ \begin{array}{l} \frac{\partial^2 \phi}{\partial x^2} = \frac{\partial^2 \phi}{\partial y^2} = -2G\theta \\ \end{array} \right.$$

$\phi = 0$ on the boundary


Stress $\left\{ \begin{array}{l} \sigma_{xz} = \frac{\partial \phi}{\partial y} \\ \tau_{yz} = -\frac{\partial \phi}{\partial x} \end{array} \right.$

$$T = 2 \iint_A \phi dx dy$$


$$\theta = T/GJ$$





For a circle:



For an ellipse:



6.32 - Equilateral Triangle Cross-Section




$$\phi = \frac{G\theta}{2h} (x - \sqrt{3}y - 2h/3) \cdot ((x + \sqrt{3}y - 2h/3) \cdot (x + h/3))$$


Define $J = \frac{h^4}{15\sqrt{3}}$

$$\tau_{max} = \frac{15\sqrt{3}}{2h^3} T \quad \theta = \frac{T}{GJ}$$

6.4 - The Prandtl elastic-membrane analogy



6.6 - Torsion of rectangular cross-section




$$\text{Define } J = k_1 (2h)^3 (2b)$$

$$\text{Then } \theta = T/GJ$$

Max shear stress ($b > h$)

$$Z_{\max} = G\theta \cdot (2h) \cdot \left(\frac{k_1}{k_2}\right)$$

The max. shear occurs at the location with the shortest distance to centre (at $x = \pm h$, $y = 0$)



b/h	1.0	2.0	$\dots \infty$
k_1	0.141	0.229	$\dots 0.333$
k_2	0.208	0.246	$\dots 0.333$

$$b/h \gg 3$$

$$k_1 \approx k_2 = 1/3 - 0.210 h/b$$


6.5 Narrow Rectangular Cross-section

$$b \geq 10h \quad h_1 = h_2 = \frac{1}{3}$$

$$J = \frac{1}{2}(2h)^3(2b)$$


$$\Theta = T/GJ$$

$$\begin{aligned}\tau_{\max} &= G\Theta \cdot 2h \cdot \frac{h_1}{h_2} = G\Theta \cdot 2h \\ &= 2G\Theta h\end{aligned}$$



Shear stresses


$$\sigma_{zx} = 0 \quad \sigma_{zy} = 2G\Theta x$$




Resultant of the shear stress
through the wall thickness
is zero.

Summation of shear stress (moment)

$$= T/2$$




$$J = \frac{1}{3}(2h)^3(2b)$$



$$2b = 2\pi r$$

$$J = (\frac{1}{3})(2\pi r)(2h)^3$$




$$\begin{aligned} J &= l_3 (2h_1)^3 (b_1) \\ &+ (l_3)(2h_2)^3 (b_2) \\ &+ (l_3)(2h_3)^3 (b_3) \end{aligned}$$

$$Z_{\max,1} = 2G\theta h_1$$

$$Z_{\max,2} = 2G\theta h_2$$


$$Z_{\max,3} = 2G\theta h_3$$

$$\therefore Z_{\max} = 2G\theta \cdot h_{\max}$$



Oct. 18 / 18


Example :




$$\begin{aligned}T_1 &= 750 \text{ N}\cdot\text{m} \\T_2 &= 400 \text{ N}\cdot\text{m} \\G &= 77.5 \text{ GPa} \\&= 77500 \text{ N/mm}^2\end{aligned}$$

Find \bar{C}_{max} and angle of twist of the free end.

Solution :



For AB:




$$\sum M_z = 0$$

$$T_1 + T_2 - T_{AB} = 0$$

$$T_{AB} = T_1 + T_2 \Rightarrow T_{AB} = 1150 \text{ N}\cdot\text{m}$$


For BC:



$$\sum M_z = 0$$

$$T_{BC} = T_2 \Rightarrow T_{BC} = 400 \text{ N}\cdot\text{m}$$

For AB:



$$\begin{aligned}2b &= 60 \quad \left\{ \frac{b}{h} = 1.5 \right. \\2h &= 40 \quad \left. \right\}\end{aligned}$$

$$1 \text{ m} = 10^3 \text{ mm} \quad \left\{ 1 \text{ N/mm}^2 = 1 \text{ MPa} \right.$$

$$1 \text{ N/m}^2 = 1 \text{ Pa} \quad \left. \right\}$$

$$\text{From table } K_1 = 0.196$$

$$K_2 = 0.231$$


$$\begin{aligned}\theta_{AB} &= \frac{T_{AB}}{GJ_{AB}} = \frac{1150 \times 10^3}{(77.5)(10^3)(752640)} \\&= 1.4716 \times 10^{-5}\end{aligned}$$

$$\begin{aligned}J_{AB} &= K_1 (2b)(2h)^3 \\&= (0.196)(60)(40)^3 \\&= 752640 \text{ mm}^4\end{aligned}$$

$$\bar{C}_{max}^{AB} = \frac{T_{AB}}{K_2 (2b)(2h)^3} = \frac{1150 \times 10^3}{(0.231)(60)(40)^2}$$

$$= 51.9 \text{ MPa}$$

For BC :




$$2b = 40$$

$$2h = 30$$

$$\frac{b}{h} = \frac{40}{30} = 1.33\bar{3}$$

$$K_1 = K_1 \left(\frac{b}{h} \right)$$



Assuming linearly distributed.

$$\frac{0.196 - 0.144}{1.5 - 1} = \frac{x - 0.144}{1.333 - 1}$$

$$x = 0.1776 = K_1$$

$$K_2 = 0.2233$$

$$\begin{aligned} J_{BC} &= K_1 (2b)(2h)^3 \\ &= (0.1776)(40)(30)^3 \\ &= 19180.8 \text{ mm}^4 \end{aligned}$$

$$\therefore \theta_{BC} = \frac{T_{BC}}{GJ_{BC}} = \frac{400(10^3)}{(77.5 \times 10^3)(19180.8)} = 2.6909(10^{-5}) \text{ rad/mm}$$

$$\bar{\epsilon}_{max}^{BC} = \frac{T_{BC}}{K_2(2b)(2h)^2} = \dots = 49.8 \text{ MPa}$$

$$\therefore \bar{\epsilon}_{max} = 51.9 \text{ MPa}$$


It occurs in the AB segment.

$$\beta_{c/A} = \beta_{c/B} + \beta_{B/A}$$


$$\beta_{c/A} = (BC \cdot \theta_{BC}) + (AB \cdot \theta_{AB})$$

$$\Rightarrow (1500)(2.6909 \times 10^{-5}) + (3000)(9.9512 \times 10^{-6}) \text{ rad}$$

Case 1 :



Case 2 :



Example : For the given I-beam :

- Find the torsional constant J
- Find the maximum torque that the beam can take if the yield shear stress is $\tau_y = 36 \text{ ksf}$.

Given $G = 12 \times 10^3 \text{ ksf}$:

→ a)

$$\begin{aligned} J &= \left(\frac{1}{3}\right)(2b)(2h)^3 \\ &\rightarrow J = \left(\frac{1}{3}\right)(12)(0.605)^3 \times 2 \dots \\ &\dots + \left(\frac{1}{3}\right)(10.91)(0.390)^3 \\ J &= 1.99 \text{ in}^4 \end{aligned}$$

$$\rightarrow b) \quad \tau_{\max} = \frac{T}{J} (2h)_{\max}$$

$$\Rightarrow \tau_{\max} = \frac{T}{J} (0.605)$$





Since $\tau_{\max} \leq \tau_y$

$$\Rightarrow \frac{\tau_{\max} (0.605)}{J} = \tau_y$$


$$\Rightarrow \tau_{\max} = \left(\frac{36 \times 1.99}{0.605} \right) \text{ ksf} - \text{in}$$

6.7 Hollow thin-wall torsion members and multiply connected cross-section.

Narrow rectangular cross-section.



- Shear stress is practically constant through the wall thickness.
- Shear stress is parallel to the boundary of the section.
- $q = \bar{C} t =$ Shear Flow
- $q = \text{const.}$



Oct. 19 / 18


Example :



(a)



(b)




(c)


→ three thin wall members, find the ratio of the largest shear stress and the ratio of the angle of twist per unit length.

Solution: b and c are the same

$$I_b = \frac{1}{3} (2\pi r) (2h)^3$$



(d)



(e)

For (a) outer radius: $r+h$

inner radius: $r-h$

$$J_a = \frac{\pi}{2} [(r+h)^4 - (r-h)^4]$$

$$\Rightarrow \frac{\pi}{2} [(r^4 + 4r^3h + 6r^2h^2 + 4rh^3 + h^4) - (r^4 - 4r^3h + 6r^2h^2 - 4rh^3 + h^4)]$$

$$\Rightarrow (\pi/2) [8r^3h + 8rh^3]$$

$$\approx 4\pi r^3 h$$

$$Z_{\max}^a = \frac{T}{J_a} \cdot (r+h) \stackrel{\text{neglect}}{=} \left(\frac{T}{4\pi r^3 h} \right) \cdot r = \frac{T}{4\pi r^2 h}$$

$$Z_{\max}^b = \frac{T}{J_b} \cdot (2h) = \left(\frac{T}{(1/3)2\pi r (2h)^3} \right) = \frac{3T}{8\pi r h^2}$$

$$\therefore \frac{Z_{\max}^a}{Z_{\max}^b} = \left(\frac{T}{4\pi r^2 h} \right) \left(\frac{8\pi r h^2}{3T} \right) \Rightarrow \left(\frac{2}{3} \cdot \frac{h}{r} \right)$$

(2)

$$\theta = \frac{T}{GJ} \rightarrow \text{where } T, G \text{ don't change.}$$

$$\therefore \frac{\theta_a}{\theta_b} = \frac{J_b}{J_a} = \frac{\left(\frac{1}{3}\right) 2\pi r (2h)^3}{4\pi r^3 h} = \frac{4}{3} \left(\frac{h}{r}\right)^2$$


A Special case :

$$r = 400 \text{ mm} \quad 2h = 30 \text{ mm}$$

$$\frac{J_{max}^a}{J_{max}^b} = \frac{2}{3} \cdot \left(\frac{15}{400}\right) = \frac{1}{40}$$

$$\frac{\theta_a}{\theta_b} = \frac{4}{3} \left(\frac{15}{400}\right)^2 = \frac{1}{1067}$$

Example



a) Find the max shear stress in terms of :

$$T, a, b, G$$




what are the percentage

errors of J_{max} and θ

$$\text{if using } J = \left(\frac{1}{3}\right)(b)(a/2)^3 = \left(\frac{1}{24}\right)a^3b$$

Solution: a)

$$J = \frac{1}{3} \int_0^b (2h)^3 ds$$



$$\Rightarrow J_{max} = \frac{T}{GJ} (2h)_{max}$$

$$\frac{s}{b} = \frac{2h}{a} \Rightarrow 2h = \frac{a}{b} \cdot s$$

$$\Rightarrow J = \frac{1}{3} \int_0^b \left(\frac{a}{b}s\right)^3 ds$$

$$= \frac{1}{3} \frac{a^3}{b^3} \int_0^b s^3 ds$$

$$= \left(\frac{1}{3}\right) \left(\frac{a^3}{b^3}\right) \left(\frac{1}{4}\right) (b^4) = \frac{1}{12} a^3 b$$

(3)

2)

$$\Rightarrow \bar{Z}_{\max} = T/J(2h)_{\max}$$

$$= \frac{T}{(\frac{1}{12})a^3b} \cdot a = \frac{12T}{a^2b}$$

$$\theta = \frac{T}{GJ} = \frac{T}{G(\frac{1}{12})a^3b} = \frac{12T}{Ga^3b}$$


b) $J = (\frac{1}{12})a^3b$

$$J_{\text{rec}} = (\frac{1}{24})a^3b$$

$$\bar{Z}_{\max}^{\text{rec}} = \frac{T}{J_{\text{rec}}} \cdot (2h)_{\max}$$



$$= \frac{T}{(\frac{1}{24})a^3b} \cdot \left(\frac{a}{2}\right)$$

$$= \frac{12T}{a^2b}$$




$$\theta = ?$$

Oct. 25 / 18






$$Z_{\max} = \frac{T}{S} (2H)_{\max}$$



$$q = Tt \quad (\text{shear flow})$$

$q = \text{const.}$ (along the cross section)

thin-wall cylinder
(closed)




$$\sum F_z = 0 :$$

$$-q_1 dz + q_2 dz \Rightarrow q_1 = q_2$$

Resultant of Shear Flow over the cross-section

Internal Force:




Internal Stress

τ

$$\sum F_x = 0, \quad \sum F_y = 0 \\ \sum M_O = T$$

(2)




$$\begin{aligned} dq \cdot ds &= q \cdot d \cdot ds \\ &= q \cdot 2S \Delta OPQ \\ \sum M_O &= q \cdot 2A = T \end{aligned}$$

A: the area enclosed by the mean
perimeter of the cross-section

$$q = Z t = \frac{T}{2A}$$

Angle of twist per unit length θ



Rotation between end sections

$$\beta = L\theta$$

$$\text{Work done is: } (\frac{1}{2})TB = (\frac{1}{2})TL\theta$$

Stress components: $\sigma_{zx} \neq 0$, $\sigma_{zy} \neq 0$

Strain energy density:

$$\begin{aligned} U_o &= \frac{1}{2E} (\sigma_{xy}^2 + \sigma_{yz}^2 + \sigma_{xz}^2) - \nu_E (\sigma_{xx}\sigma_{yy} + \sigma_{xx}\sigma_{zz} + \sigma_{yy}\sigma_{zz}) \dots \\ &\dots + \frac{1}{2G} (\sigma_{xy}^2 + \sigma_{yz}^2 + \sigma_{xz}^2) \\ &\Rightarrow \frac{1}{2G} (\sigma_{xz}^2 + \sigma_{yz}^2) \\ &\Rightarrow \frac{1}{2G} Z^2 \end{aligned}$$

Strain energy of the torsional member


$$U = \iiint_v U_o dv = \iint_A L U_o dA$$

$$= L \int \int U_o dt$$

$$= L \oint (S_o U_o dt) ds$$

$$= L \oint (S_o \frac{Z^2}{2G} dt) ds$$

$$\left. \begin{aligned} &= L \oint \frac{Z^2}{2G} t ds \\ &= L \oint \frac{Z q}{2G} ds \\ &= \frac{L q}{2G} \oint Z ds \end{aligned} \right\}$$



$$\frac{1}{2} T \zeta \theta = \frac{q}{2G} \oint \zeta ds$$

$$\text{Since } q = \frac{T}{2A} \Rightarrow \theta = \frac{q}{GT} \oint \zeta ds$$

$$\boxed{\theta = \frac{1}{2GA} \oint \zeta ds} \quad (\text{Angle of twist})$$

$$\text{Since } \zeta = \frac{q}{t}$$

$$\Rightarrow \theta = \frac{1}{2GA} \oint \frac{q}{t} ds = \frac{q}{2GA} \oint \frac{1}{t} ds$$

$$f = \frac{T}{4GA} \oint \frac{1}{t} ds$$



$$\text{Define } J = \frac{4A^2}{\oint \frac{1}{t} ds}$$

$$\Rightarrow \theta = \frac{T}{GJ}$$

Special Case: $t = \text{const.}$

$$\oint \frac{1}{t} ds = s/t \quad s: \text{the wall mean perimeter length}$$



6.7.1 Hollow thin-wall member having several compartments



$$q_1 = q_2 + q_3$$

$$\boxed{\therefore q_3 = q_1 - q_2}$$

$$\theta = \frac{1}{2GA} \oint \zeta ds$$




Compartment 1

Compartment (2):



$$\delta = \frac{1}{2GA} \oint Z ds$$

δ must be the same for either compartment.




Internal resultant:

$$T = 2A_1 q_1 + 2A_2 q_2$$



Oct. 26 / 18

Example:



$$T = 50 \text{ kip-in}$$

Find the max shear stress developed in the cross-section

Also find the effective polar moment of inertia.


Solution: $\tau = \frac{T}{2A} \rightarrow \tau = \text{mean area}$

$$A = (8 - 1/8 - 1/4) \times (6 - 1/8 - 1/8) = 43 \text{ in}^2$$

$$\therefore \tau = \frac{50 \text{ kip-in}}{(2)(43 \text{ in}^2)} \rightarrow \tau = C \cdot t \quad \therefore C_{\max} = \frac{\tau}{t_{\min}}$$

$$\therefore C_{\max} = \frac{50}{(2)(43)} \left(\frac{1}{1/4} \right) = 2.28 \text{ ksi}$$

$$J = \frac{4A^2}{\int \frac{1}{t} ds}$$



NOTE:


$$\int \frac{1}{t} ds = \int_{SP} \frac{1}{t} ds + \int_{RS} \frac{1}{t} ds$$

$$\begin{aligned} \int \frac{1}{t} ds &= \int_{SP} \frac{1}{t} ds + \int_{RS} \frac{1}{t} ds \\ &= \frac{1}{1/4} (SP + PQ + QR) + \frac{1}{1/2} (RS) \end{aligned}$$

$$t \quad \Rightarrow \int \frac{1}{t} ds = 4((8 - 1/8 - 1/4) + (6 - 1/8 - 1/8)) + (8 - 1/8 - 1/4) + 2(6 - 1/8 - 1/8) = 95.5$$

$$\text{and } J = \frac{4A^2}{\int \frac{1}{t} ds} = \frac{4 \times 43.8^2}{95.5} = 80.354 \text{ in}^2$$


2




For the open section, find J

$$\begin{aligned}
 J &= \sum \frac{1}{3} (2b)(2h)^3 \\
 &= \left(\frac{1}{3} \left[(8 - \frac{1}{8} - \frac{1}{4}) + (6 - \frac{1}{8} - \frac{1}{8}) + (8 - \frac{1}{8} - \frac{1}{4}) \right] \times (\frac{1}{4})^3 \right. \\
 &\quad \left. \dots + (\frac{1}{3})(6 - \frac{1}{8} - \frac{1}{8})(\frac{1}{2})^3 \right)
 \end{aligned}$$


$$J = 0.34896 \text{ in}^4$$



$$\begin{aligned}
 J &= J_{\text{close}} + J_{\text{open}} \\
 &= \frac{4A^2}{8t ds} + \frac{1}{3}(2b)(2h)^3
 \end{aligned}$$




$$\begin{aligned}
 J &= J_{\text{close}} + J_{\text{open}_1} + J_{\text{open}_2} \\
 &= \frac{4A^2}{8t ds} + \frac{1}{3}(2b)(2h)^3 + \frac{1}{3}(2b)(2h)^3
 \end{aligned}$$



→ Same thing.


Example :



Given $G = 26.0 \text{ GPa}$

the max shear stress is 40 MPa , find the max T the member can support.

Cell 1 :




$$\theta_1 = \frac{1}{2GA_1} \oint \tau ds = \frac{1}{2GA_1} \oint \frac{q}{\epsilon} ds$$

$$\text{Since } A_1 = 60^2 = 3600$$

$$\theta_1 = \frac{1}{2G(3600)} \left[\left(\frac{q_1}{4.5} \times 3 \times 60 \right) + \left(\frac{q_1 - q_2}{1.5} \times 60 \right) \right]$$

Cell 2 :



$$A_2 = \frac{1}{2} \pi r^2 = \left(\frac{1}{2} \right) \pi (30)^2 = 450 \pi$$

$$\theta_2 = \frac{1}{2GA_2} \oint \frac{q}{\epsilon} ds$$


$$= \frac{1}{2G(450\pi)} \left[\frac{q_2}{3} \pi (30) + \frac{q_2 - q_1}{1.5} (60) \right]$$

Since it's a rigid body, $\theta_1 = \theta_2$

$$\frac{1}{2G(3600)} \left[\frac{q_1}{4.5} \times 180 + \frac{q_1 - q_2}{1.5} \times 60 \right]$$

$$\Rightarrow \frac{1}{2G(450\pi)} \left[\frac{q_2}{3} \times 30\pi + \frac{q_1 - q_2}{1.5} (60) \right]$$

$$\Rightarrow q_1 = 1.220 q_2$$



$$T_1 = \frac{q_1}{4.5}$$


$$T_2 = \frac{q_2}{3.0}$$

$$T_3 = \frac{q_1 - q_2}{1.5}$$


$$T_{\max} = \max(T_1, T_2, T_3) = 40$$

$$T = 2A_1 q_1 + 2A_2 q_2$$

OCT. 30/18

Torsion member with restrained ends.

Shear Concentration:


Ch. 7 - Bending of straight Beams

7.1 - Fundamentals of beam bending





$$\frac{L}{D} \geq 5$$

Homogeneous and isotropic (material assumption)




no twisting (only bending deformation)




Beam has a symmetrical plane



$$\sigma_{zz} = \frac{M_x u}{I_x}$$



$$I_x = \iint_A y^2 dxdy$$




$$\sigma_{zz} = -\frac{M_y^o x}{I_y}$$

$$\Rightarrow \sigma_{zz} = \frac{M_y^o y}{I_z} - \frac{M_y^o x}{I_y}$$



(no twisting)

Forces P_x and P_y are passing through the shear center of the beam.

* Shear centre



Example :




Find the max tensile and compressive normal stress at the middle span of the beam.

Solution:

$$\left. \begin{array}{l} A = A_1 + A_2 \\ \bar{x} = \frac{A_1 \bar{x}_1 + A_2 \bar{x}_2}{A} \\ \bar{y} = \frac{A_1 \bar{y}_1 + A_2 \bar{y}_2}{A} \end{array} \right\}$$

$$I_{x'}, I_{y'}, I_{xy'} \\ \Rightarrow I_x, I_y, I_{xy}$$



Parallel axis theorem:

$$\left\{ \begin{array}{l} I_x = I_{x'} + A\bar{y}^2 \\ I_y = I_{y'} + A\bar{x}^2 \\ I_{xy} = I_{x'y'} + A\bar{x}\bar{y} \end{array} \right.$$

$$I_{x'} = \frac{1}{12}bh^3 \\ I_{y'} = \frac{1}{12}hb^3 \\ I_{xy} = 0$$

Nov. 1 / 18

$$O_1(\bar{x}_1, \bar{y}_1)$$

$$O_2(\bar{x}_2, \bar{y}_2)$$


$$\bar{y}_1 = (\frac{10}{2}) = 5$$

$$\bar{y}_2 = (\frac{50}{2}) + 10 = 35.$$

$$A_1 = (50) \times (10) = 500$$

$$A_2 = (50)(10) = 500$$

$$\therefore \bar{y} = \frac{A_1 \bar{y}_1 + A_2 \bar{y}_2}{A_1 + A_2} = \frac{500(5) + (500)(35)}{(500 + 500)} = 20$$



$$I_x = I_x^{(1)} + I_x^{(2)}$$

$$I_x^{(1)} = I_{x_1}^{(1)} + Ad^2$$


$$= (\frac{1}{12})(50)(10)^3 + (500)(20-5)^2$$

$$I_x^{(2)} = I_{x_2}^{(2)} + Ad^2$$


$$= (\frac{1}{12})(10)(50)^3 + (500)(20-35)^2$$

$$I_x = 333333.333 \text{ mm}^4$$


Statics



-z Face



Outer normal



$$\sum M_x = 0 : \quad M_x - (2250)(500) + (1500)(100) \\ M_x = 975000 \text{ N-mm}$$


Normal Stress

$$\sigma_{zz} = \frac{M_x y}{I_x}$$

At the top, $y = -20$



$$\sigma_{zz} = \frac{975000}{333334} \times (-20) = -58.8 \text{ MPa}$$

7.2 Bending Stress in Beams subjected to Non-symmetric bending



P : through shear center C
(no twisting)
(plane cross-section remain
plane)

Method of Section



$$dF_z = \sigma_{zz} dx dy$$

Resultant

$$\iint_A \sigma_{zz} dx dy = 0 \quad (\text{No axial force})$$


$$\rightarrow \iint_A y \sigma_{zz} dx dy = M_x$$

$$\iint_A x \sigma_{zz} dx dy = -M_y$$

Cross-section has a rigid body rotation

The disp. at point (x, y, z)

$$\left\{ \begin{array}{l} u = 0 \\ v = 0 \\ w = a''(z) + x b''(z) + y c''(z) \end{array} \right.$$



$$\text{Strains: } \epsilon_{xx} = 0, \epsilon_{yy} = 0$$

$$\epsilon_{zz} = \frac{\partial w}{\partial z} = a'(z) + x b'(z) + y c'(z)$$

$$\text{Stress: } \sigma_{zz} = E \epsilon_{zz} = a(z) + x b(z) + y c(z)$$

$$\iint_A \sigma_{zz} dx dy = \iint_A (a(z) + b(z)x + c(z)y) dx dy$$

$$= a(z) \iint_A dx dy + b(z) \iint_A x dx dy + c(z) \iint_A y dx dy = 0$$

$$\Rightarrow a(z) \cdot A = 0 \Rightarrow a(z) = 0$$

$$\Rightarrow \sigma_{zz} = b(z)x + c(z)y$$

$$\Rightarrow \iint_A y \sigma_{zz} dx dy = \iint_A (b(z)xy + c(z)y^2) dx dy$$

$$= b(z) \iint_A xy dx dy + (c(z)) \iint_A y^2 dx dy \dots$$

$$= b(z) \iint_A x^2 dx dy + (c(z)) \iint_A xy dx dy = -M_x$$

$$\text{Define } I_x = \iint_A y^2 dx dy$$

$$I_y = \iint_A x^2 dx dy$$

$$I_{xy} = \iint_A xy dx dy$$

$$\rightarrow \begin{cases} b(z) I_{xy} + c(z) I_x = M_y \\ b(z) I_y + c(z) I_{xy} = -M_x \end{cases}$$

$$\rightarrow b(z) = \frac{-M_y I_x + M_x I_{xy}}{I_x I_y - I_{xy}^2} \quad \Delta = I_x I_y - I_{xy}^2$$


(4)

$$\sigma_{zz} = \frac{M_x I_y + M_y I_{xy}}{\Delta} y - \frac{M_y I_x + M_x I_{xy}}{\Delta} x$$

If $I_{xy} = 0$, then $\Delta = I_x I_y$

$$\Rightarrow \boxed{\sigma_{zz} = \frac{M_x}{I_x} y - \frac{M_y}{I_y} x}$$



Nov. 6 / 18



$$I_x = 2.783 \times 10^6 \text{ mm}^4$$

$$I_y = 1.003 \times 10^6 \text{ mm}^4$$

$$I_{xy} = 0.9726 \times 10^6 \text{ mm}^4$$



Normal Stress

$$\sigma_{zz} = \frac{M_x I_y + N_y I_{xy} y}{\Delta} - \frac{M_y I_x + M_x I_{xy} x}{\Delta}$$

$$\text{Here, } \Delta = I_x I_y - I_{xy}^2$$

$$\Delta = 1.8454 \times 10^{12} \text{ (mm}^4\text{)}$$

$$M_x I_y + N_y I_{xy} = 1.8352 \times 10^{12}$$


$$M_y I_x + M_x I_{xy} = 2.6361 \times 10^{12}$$

$$\Rightarrow \sigma_{zz} = \left(\frac{1.8352 \times 10^{12}}{1.8454 \times 10^{12}} \right) y - \left(\frac{2.6361 \times 10^{12}}{1.8454 \times 10^{12}} \right) x$$

$$\sigma_{zz} = 0.99449(y - 1.4364x)$$

x, y : mm

σ_{zz} : MPa



$$y - 1.4364x = 0$$

$$\text{Let: } \tan \alpha = 1.4364$$

$$\alpha = 55.155^\circ$$


$$\left. \begin{array}{l} A(19.74, -80.26) \\ B(-60.26, 39.74) \end{array} \right\}$$

$$\sigma_A = 0.99449(-80.26 - 1.4364 \times 19.74) \\ = -108.0 \text{ MPa} \sim$$

$$\sigma_B = 0.99449(39.74 - 1.4364 \times (-60.26))$$

$$\sigma_B = 125.6 \text{ MPa}$$

$$\left[\begin{array}{l} \sigma_{zz} = \frac{M_x I_y + M_y I_{xy} y}{\Delta} \dots \\ \dots - \frac{M_y I_x + M_x I_{xy}}{\Delta} x \end{array} \right] *$$



Neutral axis:

$$\sigma_{zz} = 0$$

$$\Rightarrow \frac{M_x I_y + M_y I_{xy}}{\Delta} y - \frac{M_y I_x + M_x I_{xy}}{\Delta} x = 0$$

$$\Rightarrow y = x \tan \alpha = 0$$

$$\text{and } \tan \alpha = \frac{M_y I_x + M_x I_{xy}}{M_x I_y + M_y I_{xy}}$$


The normal stress

$$\sigma_{zz} = \frac{M_x I_y + M_y I_{xy}}{\Delta} (y - x \tan \alpha)$$

IF $M_x \neq 0$

$$\sigma_{zz} = \frac{M_x}{I_x - I_{xy} \tan \alpha} (y - x \tan \alpha)$$


7.3 Deflections of Straight Beams Subjected to nonsymmetrical bending.



2
↓

Normal Strain

$$\epsilon_{zz} = \frac{(R_y + y) d\theta_x - dz}{dz} = \frac{y}{R_y}$$



$$\frac{1}{R_y} = \frac{\left| \frac{\partial^2 v}{\partial z^2} \right|}{\left(\sqrt{1 + \left(\frac{\partial v}{\partial z} \right)^2} \right)^3}$$

Small deformation

$$\left| \frac{\partial v}{\partial z} \right| \ll 1$$

$$\Rightarrow \frac{1}{R_y} = \left| \frac{\partial^2 v}{\partial z^2} \right| = - \frac{\partial^2 v}{\partial z^2}$$

$$\Rightarrow - \frac{\partial^2 v}{\partial z^2} = \frac{\epsilon_{zz}}{y} = \frac{\bar{\epsilon}_{zz}}{E_y}$$

Since $\bar{\epsilon}_{zz} = \frac{M_x I_y + M_y I_{xy} y}{\Delta} - \frac{M_y I_x + M_x I_{xy} x}{\Delta}$

Let $x = \theta$:

Then :
$$\boxed{- \frac{\partial^2 v}{\partial z^2} = \frac{M_x I_y + M_y I_{xy}}{E \Delta}}$$

Special case : $I_{xy} = 0$

then $\Delta = I_x I_y$


$$\Rightarrow \boxed{- \frac{\partial^2 v}{\partial z^2} = \frac{M_x}{EI_x}} \quad - EI v'' = M$$

The total deflection:



$$u = -v \tan \alpha$$

$$\delta = \sqrt{u^2 + v^2}$$

Example



Given $E = 72 \text{ GPa}$



Find the max deflection of the beam

Solution $y_0 = 82.0 \text{ mm}$


$$I_x = 39.69 \times 10^6 \text{ mm}^4$$

$$I_y = 30.73 \times 10^6 \text{ mm}^4$$

$$I_{xy} = 0$$

(1)

Nov. 8 / 18



$$\frac{-\partial^2 V}{\partial z^2} = \frac{Mx}{EIz}$$



For unsymmetrical beam bending

$$\frac{-\partial^2 V}{\partial z^2} = \frac{Mx I_y + M_y I_x}{EI}$$

$$\frac{-\partial^2 V}{\partial x^2} = \frac{Mx}{E(I_x - I_y \tan \alpha)}$$

Since $I_{xy} = 0$:

$$\frac{-\partial^2 V}{\partial x^2} = \frac{Mx}{EIz}$$


 Mx is a function of z (And $P = 35 \text{ kN}$)Since $P_y = P \cos(10^\circ)$

$$V_{\max} = \frac{P_y L^3}{48 EI_z} \quad \text{From table}$$

$$V_{\max} = \frac{PL^3 \cos(10^\circ)}{48 E I_z}$$

$$V_{\max} = \frac{(35 \times 10^3)(3 \times 10^4)(\cos 10^\circ)}{(48)(72 \times 10^3)(39.69 \times 10^4)}$$

$$= 6.78 \text{ mm}$$



$$\tan \alpha = \frac{M_y I_x + M_x I_{xy}}{M_x I_y + M_y I_{xy}}$$

$$M_y = \left(\frac{1}{2}\right) P_x \cdot \left(\frac{1}{2}\right) = \frac{1}{4} P (\sin 10^\circ) L$$

$$M_x = \left(\frac{1}{2}\right) P_y \cdot \left(\frac{1}{2}\right) = \frac{1}{4} P (\cos 10^\circ) L$$

$$\tan \alpha = \frac{M_y I_x}{M_x I_y} = \frac{\left(\frac{1}{4}\right) L \sin(10^\circ) \times 39.69 \times 10^4}{\left(\frac{1}{4}\right) L \cos(10^\circ) \times 30.73 \times 10^4} = 0.227$$

$$\alpha = 12.83^\circ$$


 \therefore max deflection

$$\delta_{\max} = \frac{V_{\max}}{\cos \alpha} = \frac{6.78}{\cos(12.83^\circ)} = 6.95 \text{ mm}$$


Ch. 8 - Shear Center For Thin-wall beam Cross-section

8.1 Approximation for shear in thin-wall cross section.

Shear center : A point in the cross-section of a beam through which the loads must pass for the beam to be subjected to only bending deformation. No torsion is caused by the transverse loads that act through the shear center.



Shear stress in the thin wall :




1° Shear stress is parallel to the boundary

2° Shear stress is uniform through the wall thickness

The resultant of the shear stress through the wall thickness : $q = \tau t$ (shear flow)



8.2 Shear Flow in Thin-wall beam Cross-section

① Shear stress in a general cross-section



$$\sum M_y = 0 : M_y + dM_y - M_y + V_x dz = 0$$

$$\frac{dM_y}{dz} = -V_x$$




$$\sum F_z = 0 : - \iint_{A'} \sigma_{zz} + dx dy + \iint_{A'} (\sigma_{zz} + d\sigma_{zz}) dx dy$$

$$-C dz \cdot t = 0$$

$$\therefore C \cdot t = g = \iint_{A'} \frac{d\sigma_{zz}}{dz} dx dy$$


(1)

Nov. 9 / 18



Find the location and magnitude of the max normal stress in the beam.


Solution:




$$\angle M_y = \emptyset$$

$$M_y - 5.333 \times 2 = \emptyset$$

$$M_y = 10.667 \text{ KN}\cdot\text{m}$$




$$M_x = 10.667 \text{ KN}\cdot\text{m}$$




Observation, max normal occurs between $z=2, z=4$

when $2 \leq z \leq 4$

$$\begin{cases} M_x(z) = \frac{10.667}{4} z \\ M_y(z) = (6-z)\left(\frac{10.667}{4}\right) \end{cases}$$




$$\begin{aligned} \text{Since } I_x = I_y &= \left(\frac{1}{4}\right) \pi r^4 \\ &= \left(\frac{1}{4}\right) \pi (37.5)^4 \\ &= 1.553 \times 10^6 \text{ mm}^4 \end{aligned}$$



$$2 \leq z \leq 4$$

$$\therefore \tan \alpha = \frac{M_y I_x + M_x I_{xy}}{M_x I_y + M_y I_{xy}} = \frac{M_y}{M_x} \Rightarrow \boxed{\tan \alpha = \frac{6-z}{z}}$$

(2)



$$P(r \sin \alpha, -r \cos \alpha)$$

$$Q(-r \sin \alpha, r \cos \alpha)$$

Normal Stress

$$\sigma_{zz} = \frac{M_x I_y + M_y I_{xy}}{\Delta} - \frac{M_y I_x + M_x I_{xy}}{\Delta} x$$

(where $\Delta = I_x I_y$)

(where $I_{xy} = 0$
for circular cross-section)

$$= \frac{M_x}{I_x} y - \frac{M_y}{I_x} x$$

OR

$$\sigma_{zz} = \frac{M_x(y - x \tan \alpha)}{I_x - I_{xy} \tan^2 \alpha}$$

can use either way

$$\sigma_{zz} = \frac{(M_x)^2}{I_x} (y - x \tan \alpha)^2$$

const.

$$\sigma_{zz,P} = \frac{M_x}{I_x} (-r \cos \alpha - r \sin \alpha \cdot \tan \alpha)$$


$$= -\frac{M_x r}{I_x} \cdot \frac{1}{\cos \alpha}$$

$$\sigma_{zz,Q} = \frac{M_y}{I_x} (r \cos \alpha - (-r \sin \alpha) \cdot \tan \alpha)$$

$$= \frac{M_x r}{I_x} \cdot \frac{1}{\cos \alpha}$$

$$\therefore \sigma_{zz,max}^{(2)} = \frac{M_x r}{I_x} \cdot \frac{1}{\cos \alpha}$$


$$\text{Since } M_x = \frac{10.667}{4} Z \text{ KN} \cdot \text{m} = \frac{10.667}{4} Z \times 10^3$$



$$I_x = 1.553 \times 10^6 \text{ mm}^4$$

$$r = 37.5 \text{ mm}$$

$$\tan \alpha = \frac{6-Z}{Z}$$



$$\cos \alpha = \frac{Z}{\sqrt{(6-Z)^2 + Z^2}} \rightarrow \frac{Z}{\sqrt{(6000-Z)^2 + Z^2}}$$

$$\therefore \sigma_{zz}(Z) = \frac{(10.667) Z \times 10^3}{4} \times \frac{(37.5)}{(1.553 \times 10^6)} / \frac{Z}{\sqrt{(6000-Z)^2 + Z^2}}$$

$$\therefore \sigma_{zz}(Z) = 64.39 \times 10^3 \times \sqrt{(6000-Z)^2 + Z^2}$$

when $2000 \text{ mm} \leq Z \leq 4000 \text{ mm}$

min occurs @ 3000 mm

max occurs @ 2000 mm, 4000 mm


$$\sigma_{zz}(2000) = \sigma_{zz}(4000)$$

$$\Rightarrow 288.0 \text{ MPa}$$

$$\text{AT } Z=2000 \quad \tan \alpha = \frac{6000-Z}{Z} = 2$$

$$Z=4000 \quad \tan \alpha = \frac{6000-Z}{Z} = 4/2$$


Nov. 13 / 18



$$\sum F_z = 0 :$$

$$\iint_{A'} (\sigma_{zz} + d\sigma_{zz}) dx dy - \iint_{A'} \sigma_{zz} dx dy - Zt dz = 0$$

$$= q = Zt = \iint_{A'} \frac{d\sigma_{zz}}{dz} dx dy$$



$$\text{Since } \sigma_{zz} = \frac{M_x I_y + M_y I_{xy}}{\Delta} y - \frac{M_y I_x + M_x I_{xy}}{\Delta} x$$

$$\Rightarrow \frac{d\sigma_{zz}}{dz} = \frac{\frac{dM_x}{dz} I_y + \frac{dM_y}{dz} I_{xy}}{\Delta} y - \frac{\frac{dM_y}{dz} I_x + \frac{dM_x}{dz} I_{xy}}{\Delta} x$$


$$\text{because of: } \frac{dM_x}{dz} = V_y \quad \frac{dM_y}{dz} = -V_x$$

$$\Rightarrow \frac{d\sigma_{zz}}{dz} = \frac{V_y I_y - V_x I_{xy}}{\Delta} y - \frac{-V_x I_x + V_y I_{xy}}{\Delta} x$$

$$= \frac{V_y I_y - V_x I_{xy}}{\Delta} y + \frac{V_x I_x + V_y I_{xy}}{\Delta} x$$

$$\Rightarrow q = Zt = \iint_{A'} \frac{d\sigma_{zz}}{dz} dx dy$$

$$= \frac{V_y I_y - V_x I_{xy}}{\Delta} \iint_{A'} y dx dy + \frac{V_x I_x - V_y I_{xy}}{\Delta} \iint_{A'} x dx dy$$



$$\iint_{A'} y dxdy = A' \bar{y}$$



$$\iint_{A'} x dxdy = A' \bar{x}$$

$$q = \tau t = \frac{V_y I_y + V_x I_{xy}}{\Delta} A' \bar{y} + \frac{V_x I_x + V_y I_{xy}}{\Delta} A' \bar{x}$$


IF $I_{xy} = 0$, $q = (V_y / I_y) A' \bar{y} + (V_x / I_x) A' \bar{x}$

IF $V_x = 0$, $q = (V_y / I_y) A' \bar{y}$

2. Thin-Wall open section




- 1° $\tau_n = 0$ (thickness very small)
- 2° τ_s is uniform through thickness of the wall
- 3° $q = \tau t$: shear flow
- 4° Shear flow is zero at the free edge




Positive Shear Flow:


the shear flow points into the area



Example: Determine the shear flow in a C channel section due to a shear force V_y through its shear center.




$$(t \ll a)$$



$$q = Zt = \frac{V_y}{I_x} A' \bar{y}'$$

$$I_x = \left(\frac{1}{12}\right)t(2a)^3 + \left[\left(\frac{1}{12}\right)(a)t^3 + at \cdot a^2\right] \times 2 \\ = \left(\frac{8}{3}\right)a^3 t \quad (at^3 \ll a^3 t)$$

On AB:



$$A' = s \cdot t$$

$$\bar{y}' = -a$$

$$q(s.) = \frac{V_y}{I_x} A' \bar{y}'$$



$$= \frac{V_y}{8/3 a^3 t} (s \cdot t)(-a) = -\frac{3V_y}{8a^2} (s.)$$

(when $0 \leq s. \leq a$)

$$\text{at } B, \quad s. = a$$

$$q_B = -\frac{3V_y}{8a^2} (a) = -\frac{3V_y}{8a}$$

On BD:



$$\begin{aligned} g(S_2) &= g_B + \frac{V_y}{I_x} A_2 \bar{y}_2' \\ &\Rightarrow -\frac{3V_y}{8a} - \frac{V_y}{8/3 a t} \cdot (S_2 t)(a - S_2/2) \\ &= \frac{3V_y}{8a} \left(\frac{1}{2} \left(\frac{S_2}{a} \right)^2 - \frac{S_2}{a} - 1 \right) \end{aligned}$$

$$A_2 = S_2 t$$

$$\bar{y}_2' = -(a - S_2/2)$$


$$A + D_1, S_2 = 2a$$

$$g_D = g(2a) - \frac{3V_y}{8a} = g_0$$

(1)

Nov. 15 / 18

On DE



$$q(S_3) = (V_g / I_x) A' \bar{g}'$$

$$A' \bar{g}' = A'_1 \bar{g}_1 + A'_2 \bar{g}_2 + A'_3 \bar{g}_3$$


$$\begin{aligned} q(S_3) &= \frac{V_g}{I_x} [A'_1 \bar{g}_1 + A'_2 \bar{g}_2 + A'_3 \bar{g}_3] \\ &= q_D + \frac{V_g}{I_x} A'_3 \bar{g}_3 \end{aligned}$$

$$q(S_3) = -\frac{3V_g}{8a} + \frac{V_g}{8a^3 t} S_3 t$$

$$= -\frac{3V_g}{8a} + \frac{3V_g}{8a} \cdot \frac{S_3}{a}$$

@ E, $S_3 = a$

$$\therefore q_E = -\frac{3V_g}{8a} + \frac{3V_g}{8a} = 0$$



$$\text{Since } q_B = \frac{3V_g}{8a}$$

$$\begin{aligned} \therefore F_1 &= \frac{1}{2} q_B \cdot AB \\ &= \frac{1}{2} \left(\frac{3V_g}{8a} \right) a = \frac{3}{16} V_g \end{aligned}$$


D is the moment center

$$F_1 \cdot 2a = V_g e$$

$$\Rightarrow e = \frac{F_1 \cdot 2a}{V_g} = \frac{\frac{3}{16} V_g \cdot 2a}{V_g} = \frac{3a}{8}$$

negative

$$F_2 = - \underbrace{\int_{S_0}^{S_2} q(S_2) dS_2}_{\text{shaded area}}$$



$$\int_{x_0}^{x_2} f(x) dx = \frac{x_2 - x_0}{6} (f_0 + 4f_1 + f_2)$$


$$f_0 = f(x_0), f_1 = f\left(\frac{x_0 + x_2}{2}\right)$$

$$f_2 = f(x_2)$$

(2)

$$F_2 = \frac{2a}{6} (q_B + 4q_G + q_o) \\ = \frac{a}{3} \left(-\frac{3V_g}{8a} - 4\left(\frac{9V_g}{16a}\right) - \frac{3V_g}{8a} \right) \\ F_2 = -V_g$$

Example: Find the Shear Center of a C-section.



$$t = 4 \text{ mm}$$


Solution: 1° Find the centroid and moment of area about centroid axes

$$I_x = 1.733 \times 10^6 \text{ mm}^4$$

$$I_y = 0.876 \times 10^6 \text{ mm}^4$$

$$I_{xy} = -0.500 \times 10^6 \text{ mm}^4$$

2° Find internal shear flow due to the internal shear forces V_x and V_y



$$\text{At } 0 \leq s \leq 50$$

$$A' = St$$

$$\text{Centroid } O(5/2 - 25, -60)$$

$$\therefore q(s) = \frac{V_y I_y - V_x I_{xy}}{\Delta} A' G' + \dots \\ \dots + \frac{V_x I_x - V_y I_{xy}}{\Delta} A' G'$$

$$\Rightarrow V_y (0.876)(10^6) - V_x (-0.500)(10^6).S(4)(-60) \\ (1.268 \times 10^{12})$$

$$\dots - V_x (1.733)(10^6) - V_y (-0.500)(10^6) S(4)(5/2 - 25) \\ (1.268 \times 10^{12})$$


$$\Rightarrow V_x [2.733(5 - 50) - 94.635](10^6) + V_y [0.7885(5 - 50) - 165.795](10^6)$$

Resultant on AB:

$$F = \int_0^{50} q(s) ds$$


$$= -(0.1752 V_x + 0.2237 V_y)$$

$$\text{B} \quad \leftarrow \quad \text{A} \quad F = 0.1752 V_x + 0.2237 V_y$$



$$\sum M_D = (0.1752 V_x + 0.2237 V_y)(100)$$

$$= 17.52 V_x + 22.37 V_y$$




Shear Force V_x and V_y

$$\sum M_D = V_x e_y + V_y e_x$$

$$\Rightarrow \begin{cases} e_y = 17.52 \text{ mm} \\ e_x = 22.37 \text{ mm} \end{cases}$$

Nov. 16 / 18

Example Box Beam
 \rightarrow 4° cond'd

$$\begin{aligned} q_p &= q_A + \frac{V_y}{I_x} A \bar{y} \\ &= q_A + (300)(10)(-250) \\ &= q_A - 750000 \end{aligned}$$

$$\begin{aligned} q_Q &= q_p + \frac{V_y}{I_x} A \bar{y} \\ &= (q_A - 750000) + (250)(20)(-125) \\ &= q_A - 1375000 \end{aligned}$$

$$\begin{aligned} q_R = q_p ; \quad q_B &= q_A \\ \rightarrow q_s &= q_B + \frac{V_y}{I_x} A \bar{y} \\ &= q_A + (250)(10)(125) \\ &= q_A + 313500 \end{aligned}$$



1° thin wall

2° X-axis is symmetric axis

3° only internal shear force

 V_y is neededTake $V_y = I_x$

4° cut at point A



Angle of twist (per unit length) :

$$\theta = \frac{1}{2G_I} \oint q/t \, dl = \phi$$

$$\Rightarrow \int_{AP} q/t \, dl + \int_{PR} q/t \, dl + \int_{RB} q/t \, dl + \int_{BA} q/t \, dl$$

$$\Rightarrow \frac{1}{10} \int_{AP} q \, dl + \frac{1}{20} \int_{PR} q \, dl + \frac{1}{10} \int_{RB} q \, dl + \frac{1}{10} \int_{BA} q \, dl$$

$$\int_{AP} q \, dl = \frac{1}{2}(q_A + q_P)(AP) = \frac{1}{2}(q_P + q_A - 750000)(300) = 300q_A - 112500000$$

$$\begin{aligned}
 \int_{PA} q dl &= \frac{PR}{6} (q_p + 4q_Q + q_R) \\
 &= \frac{500}{6} (q_A - 750000 + 4(q_A - 1375000) + q_A - 750000) \\
 &= 500 q_A - 20(2916667) \\
 \int_{RB} q dl &= \frac{1}{2} (q_A + q_B)(RB) \\
 &= 300 (q_A) - 112500000 \\
 \int_{BS} q dl &= \frac{AB}{6} (q_B + 4q_S + q_A) \\
 &= 500 (q_A) + 10416667 \times 10 \\
 \Rightarrow & \left(\frac{1}{10} \right) (300 q_A - 112500000) \\
 &+ \left(\frac{1}{20} \right) (500 q_A - 20(2916667)) \\
 &+ \left(\frac{1}{10} \right) (300 q_A - 112500000) \\
 &+ \left(\frac{1}{10} \right) (500 q_A + 104166670) = 0
 \end{aligned}$$


$$\Rightarrow q_A = 305556 \text{ N/mm}$$

$$\rightarrow q_p = -4444444 \text{ N/mm}$$

$$q_R = -4444444 \text{ N/mm}$$

$$q_B = 305556 \text{ N/mm}$$

$$\begin{cases} q_Q = -1069444 \text{ N/mm} \\ q_S = 618056 \text{ N/mm} \end{cases}$$



1° Symmetrical?

2° Edge (Parallel) Shear Force

\Rightarrow quadratic

3° Edge (perpendicular) Shear Force

\Rightarrow linear



Finding shear center (using Point A)

A : moment center


$$e = 203.0 \text{ mm}$$

Here $I_x = 6875000000 \text{ mm}^4$



Nov. 20/18

Find shear flow on AB

D is the moment center

Find shear flow on ABThe resultant on AB

$$\begin{aligned} F &= \int_A^B q(s) ds \\ &= C_1 V_x + C_2 V_y \end{aligned}$$

 C_1 and C_2 are constantsIf F is positive,


Method 2 :

Step 1: Consider Shear Force V_x only↳ identify the line of action of V_x Step 2: Consider V_y only↳ identify the line of action of V_y

Chapter 9 - Curved Beams


9.1 - Introduction

Crane hook:



9.2 Circumferential stresses in a curved beam


- Geometry:
- ① The cross-section has a symmetric axis, and the beam has a symmetric plane
 - ② The area of cross-section is constant through the axis of the beam.




$$\frac{R}{h} > 5 \Rightarrow \text{straight beam theory}$$


Deformation:

1° Plane cross-sections remain plane after loading

2°  sigma_yy and sigma_xy are sufficiently small



(3)



Due to the rotation

$$PQ \rightarrow PQ'$$

$$PQ = r d\theta$$

$$QQ' = TQ \cdot d\phi$$

$$TQ = R_n - r$$

$$QQ' = (R_n - r) d\phi$$


The normal strain of the line segment PQ

$$\epsilon_{\theta\theta} = \frac{QQ'}{PQ} = \frac{(R_n - r) d\phi}{r d\theta}$$

Define

$$\omega = d\phi / d\theta \Rightarrow \epsilon_{\theta\theta} = \frac{R_n - r}{r} \omega$$

$$\text{Stress: } \sigma_{\theta\theta} = E \epsilon_{\theta\theta} = E \omega \frac{R_n - r}{r}$$

Statics: Cross-section BC

$$\left\{ \begin{array}{l} N = \iint_A \sigma_{\theta\theta} dA \\ M = \iint_A \sigma_{\theta\theta} (R - r) dA \end{array} \right.$$

Sub $\iint_A \sigma_{\theta\theta}$ into the above eqns

$$\left\{ \begin{array}{l} \iint_A E \omega \frac{R_n - r}{r} dA = N \\ \iint_A E \omega \frac{R_n - r}{r} (R - r) dA = M \end{array} \right. \Rightarrow E \omega = \frac{Am}{A(R - r)} \cdot M - \frac{N}{A}$$

2

$$\left\{ \begin{array}{l} Ew = \frac{A_m}{A(RA_m - A)} \cdot M - \frac{N}{A} \\ R_n = \frac{MA}{MA_m + N(A - RA_m)} \end{array} \right.$$


Here, $A_m = \iint_A \frac{1}{r} dA$

$A = \iint_A dA$ area of cross section

$$\Rightarrow \sigma_{\theta\theta} = \frac{N}{A} + \frac{M}{A(RA_m - A)} \left(\frac{A}{r} - A_m \right)$$


Calculate A_m :

$$A_m = \iint_A \frac{1}{r} dA$$



$$= \int_a^b \frac{1}{r} b \cdot dr = b \ln(c/a)$$

Nov. 22 / 18

 D : moment center

Internal shear forces are positive

Step 1: Positive shear force V_x

if Shear flow is positive, the line of action
of V_x is above D

$$e = \frac{AB}{6} (q_A + 4q_G + q_B) \times BD$$

$$V_x$$

$$q = \frac{V_y I_g - V_x I_{xy} A' \bar{y}'}{\Delta} + \frac{V_x I_x - V_y I_{xy} A' \bar{x}'}{\Delta}$$


$$(V_y = 0)$$

$$q = -\frac{V_x I_{xy} A' \bar{y}'}{\Delta} + \frac{V_x I_x A' \bar{x}'}{\Delta}$$

$$\text{At } G, A' = 0.5s$$

$$\bar{x}' = \frac{3}{4} + \frac{2}{3} = \frac{17}{12}$$

$$\bar{y}' = -\frac{4}{3}$$



$$q_G = 0.02944 V_x$$


$$\text{At } B, q_B = -0.01674 V_x$$

$$\text{the resultant } F = \frac{AB}{6} (q_A + 4q_G + q_B) = 0.01684 V_x$$


red line, distance

$$e = \frac{F \times BD}{V_x} = 0.03368 \text{ in}$$

Step 2 : Positive internal shear force V_y



The resultant shear flow on AB F_z ,
IF F_z is positive,



M : internal bending moment

A : area of cross-section [$A = th$]

R : centroidal radius

$$A_m = \iint_A \frac{1}{r} dA$$

$$\rightarrow = th \left(\frac{R+h/2}{R-h/2} \right)$$

$$\text{Case : } \frac{R}{h} = 1$$

$$\text{Inner radius : } a = R - \frac{h}{2} = \frac{h}{2}$$

$$\text{Outer radius : } b = R + \frac{h}{2} = \frac{3h}{2}$$

$$\Rightarrow b = 3a$$

$$\sigma_{xy} = \frac{M}{th(h+\ln(3)-th)} \left(\frac{th}{r} - th\ln(3) \right)$$

$$\sigma_{xy} = \frac{M}{th^2(\ln 3 - 1)} \left(\frac{h}{r} - \ln(3) \right)$$

$$\text{At inner surface, } r = a = \frac{h}{2} \quad 2$$

$$\begin{aligned}\sigma_{\text{max}} &= \frac{M}{th^2} \cdot \frac{1}{\ln(3)-1} (2-\ln 3) \\ &= 2.28518 \frac{M}{th^2} \quad \Leftarrow \text{approximate solution}\end{aligned}$$


Elasticity:

$$\begin{aligned}\sigma_{\text{max}} &= \frac{4M}{Q} \left[\frac{-a^2 b^2}{r^2} \ln\left(\frac{b}{a}\right) + b^2 \ln\left(\frac{r}{b}\right) + a^2 \ln\left(\frac{a}{r}\right) + b^2 - a^2 \right] \\ Q &= 4a^2 b^2 / \ln\left(\frac{b}{a}\right)^2 - (b^2 - a^2)\end{aligned}$$

$$\text{at } r = a$$



$$\sigma_{\text{max}} = 2.29199 \frac{M}{th^2} \quad \Leftarrow \text{exact solution}$$

Straight Beam Theory:



$$\begin{aligned}\sigma_{\text{max}} &= \frac{M}{I} \cdot \frac{h}{2} = \frac{M}{\frac{1}{12} th^3} \cdot \frac{h}{2} \\ &= 6 \frac{M}{th^2}\end{aligned}$$

Composite area:



$$A_m = \iint \frac{1}{r} dA$$


$$A_m = b \ln\left(\frac{c}{a}\right)$$

$$= A_m = \iint_{A_1} \frac{1}{r} dA + \iint_{A_2} \frac{1}{r} dA$$


$$\rightarrow A_m = A_{m1} + A_{m2}$$

$$R = \frac{A_1 R_1 + A_2 R_2}{A_1 + A_2}$$

Example :




$$a = 30 \text{ mm}$$



Determine the value of the max tensile and max compressive stresses in the frame.

Solution : BC

Internal Forces in the cross-section BC



$$\Rightarrow R = 30 + (50/2) = 55 \text{ mm}$$

$$\Rightarrow N = P = 9.50 \text{ kN} = 9500 \text{ N}$$

$$M = P(100 + 55) = 1472500 \text{ N} \cdot \text{mm}$$

Geometry

$$R = 55 \text{ mm}$$

$$A = 50 \times 50 = 2500 \text{ mm}^2$$

$$A_m = b h (c/a) = 50 h \left(\frac{80}{30}\right)$$

$$\Rightarrow A_m = 49.0415 \text{ mm} \text{ (use all decimals)}$$

Normal stress

$$\sigma_{\text{xx}} = \frac{N}{A} + \frac{M}{A(RA_m - A)} \left(\frac{R}{r} - A_m \right)$$

$$= \frac{9500}{2500} + \frac{1472500}{(2500)(55 \times 49.0415 - 2500)} \times \left(\frac{2500}{r} - 49.0415 \right)$$

r : mm

σ_{xx} : MPa

(5)

$$\text{At } r = a = 30 \text{ mm}$$


$$\sigma_{\theta\theta} = 3.8 + 2.9856 \left(\frac{2500}{30} - 49.0415 \right) \\ = 106.2 \text{ MPa}$$

$$\text{At } r = 30 + 50 = 80 \text{ mm}$$

$$\sigma_{\theta\theta} = 3.8 + 2.9856 \left(\frac{2500}{80} - 49.0415 \right) \\ = -49.3 \text{ MPa}$$


1° neutral axis? $R_n = 52.3355 \text{ mm}$

2° distribution of $\sigma_{\theta\theta}$ in the radial direction




Example:

Nov. 23/18




$$\gamma = 500 \text{ MPa}$$

$$SF = 2.00$$



Find the max load the crane hook can support

Solution: A, R, Am (Pg 324-325)




$$A_1 = \frac{\pi b h}{2} = \frac{\pi (44)(24)}{2}$$

$$A_1 = 1658.76$$

$$R_1 = a - \frac{4h}{3\pi} = 84 - \frac{(4)(24)}{(3\pi)} = 73.81$$

$$A_{m1} = 2b + \frac{\pi b}{h}(a - \sqrt{a^2 - h^2}) - \frac{2b}{h}\sqrt{a^2 - h^2} \arcsin\left(\frac{h}{a}\right) = 22.64$$

For area 2:



$$a = 24 + 60 = 84$$


$$c = 100 + a = 184$$

$$b_1 = 88, b_2 = 34$$

$$A_2 = 8100$$

$$R_2 = 196.62$$


$$A_{m2} = 50.57$$



(2)

Area 3

→ circular arc



$$AC = b$$

$$CD = b - 5$$

$$AD = \sqrt{2}(34) = 17$$

$$\Delta ACD : AC^2 = AD^2 + CD^2$$

$$b^2 = 17^2 + (b-5)^2$$

$$\Rightarrow b = 31.4$$

$$\sin \theta = \frac{AD}{AC} = \frac{17}{31.4} \Rightarrow \theta = 32.78^\circ$$

$$\text{and } \alpha = 100 + 24 + 60 - (31.4 - 5)$$

$$= 157.6 > b = 31.4$$

$$A_3 = 115.27$$

$$R_3 = 186.01$$

$$Am_3 = 0.62$$


For the cross section:

$$A = A_1 + A_2 + A_3 = 7874.03 \text{ mm}^2$$

$$Am = Am_1 + Am_2 + Am_3 = 73.83 \text{ mm}$$


$$R_c = \frac{A_1 R_1 + A_2 R_2 + A_3 R_3}{A} = 116.37 \text{ mm}$$

Statics:



...

NOV. 27

Statics

$$N = P$$

$$M = PR^2$$

$$f_B = \frac{N}{A} + \frac{M}{A(RA_m - A)} \cdot \left(\frac{A}{r_B} - A_m \right) = 0.001309 P$$

$$f_c = \frac{N}{A} + \frac{M}{A(RA_m - A)} \cdot \left(\frac{A}{r_c} - A_m \right) = -0.000535 P$$

$$\therefore G_{\max} = 0.001309 P$$

$$G_s/F_s = 0.001309 P$$

$$500/\alpha = 0.001309 P$$

$$P = 190900 N$$

Chapter 11 : The thick-wall cylinder

Geometry : A thick wall cylinder

wall thickness is constant


* closed cylinder : with end caps

* open cylinder : w/o end caps

Loading : Internal pressure P_i External pressure P_e Axial load, P Temperature Change $\Delta T (r)$

Deformation : axisymmetric :

$$P(x,y,z) \Rightarrow P(r,\theta,z)$$



(2)

$$\begin{cases} u = u(r, z) \\ v = 0 \\ w = w(r, z) \end{cases}$$

Consider the cross-section far away from the end caps:

$$\begin{cases} u = u(r) \\ v = 0 \end{cases}$$

$$\epsilon_{zz} = \frac{\partial w}{\partial z} = \text{const.}$$

Disp-strain:

$$\epsilon_{rr} = \frac{\partial u}{\partial r} = \frac{du}{dr}$$

$$\epsilon_{\theta\theta} = \frac{1}{r} \frac{\partial u}{\partial \theta} + \frac{u}{r} = \frac{u}{r}$$

$$\epsilon_{zz} = \text{const.}$$

$$\epsilon_{r\theta} = \frac{1}{2} \left(\frac{1}{r} \frac{\partial u}{\partial \theta} + \frac{\partial v}{\partial r} - \frac{\partial v}{\partial \theta} \right) = 0$$

$$\epsilon_{rz} = \frac{1}{2} \left(\frac{\partial u}{\partial z} + \frac{1}{r} \frac{\partial w}{\partial z} \right) = 0$$

$$\epsilon_{zr} = \frac{1}{2} \left(\frac{\partial u}{\partial z} + \frac{\partial v}{\partial r} \right) = 0$$

Compatibility equation

$$\frac{d}{dr}(r \epsilon_{\theta\theta}) = \epsilon_{rr}$$

Hooke's Law

$$\begin{cases} \epsilon_{rr} = \frac{1}{E} (\sigma_{rr} - \nu(\sigma_{\theta\theta} + \sigma_{zz})) + \alpha \Delta T \\ \epsilon_{\theta\theta} = \frac{1}{E} (\sigma_{\theta\theta} - \nu(\sigma_{zz} + \sigma_{rr})) + \alpha \Delta T \\ \epsilon_{zz} = \frac{1}{E} (\sigma_{zz} - \nu(\sigma_{\theta\theta} + \sigma_{rr})) + \alpha \Delta T = \text{const.} \end{cases}$$

Equilibrium eqns:

$$\frac{\partial \sigma_{rr}}{\partial r} + \frac{1}{r} \frac{\partial \sigma_{\theta\theta}}{\partial \theta} + \frac{\partial \sigma_{zz}}{\partial z} + \frac{\sigma_{rr} - \sigma_{\theta\theta}}{r} = 0$$

$$\Rightarrow \frac{\partial \sigma_{rr}}{\partial r} + \frac{\sigma_{rr} - \sigma_{\theta\theta}}{r} = 0$$


$$\frac{\partial \sigma_{\theta\theta}}{\partial r} + \frac{1}{r} \frac{\partial \sigma_{\theta\theta}}{\partial \theta} + \frac{\partial \sigma_{zz}}{\partial z} + \frac{2\sigma_{rz}}{r} = 0$$

$$\frac{\partial \sigma_{rz}}{\partial r} + \frac{1}{r} \frac{\partial \sigma_{\theta\theta}}{\partial \theta} + \frac{\partial \sigma_{zz}}{\partial z} + \frac{\sigma_r}{r} = 0$$

Boundary Conditions :

$$\text{At } r=a, \sigma_{rr} = -P_1$$

$$\text{At } r=b, \sigma_{rr} = -P_2$$



\Rightarrow Find $\sigma_{rr}, \sigma_{\theta\theta}, \sigma_{zz}, u$ and w

Solution for constant temperature :

$$\sigma_{rr} = \frac{P_1 a^2 - P_2 b^2}{b^2 - a^2} - \frac{a^2 b^2}{r^2(b^2 - a^2)} (P_1 - P_2)$$

$$\sigma_{\theta\theta} = \frac{P_1 a^2 - P_2 b^2}{b^2 - a^2} - \frac{a^2 b^2}{r^2(b^2 - a^2)} (P_1 - P_2)$$

$$\sigma_{zz} = \frac{P_1 a^2 - P_2 b^2}{b^2 - a^2} + \frac{P}{\pi(b^2 - a^2)}$$

$$u = \frac{r}{E(b^2 - a^2)} \left[(1-2v)(P_1 a^2 - P_2 b^2) + (1+v) \left(\frac{a^2 b^2}{r} \right) (P_1 - P_2) - \frac{vP}{\pi} \right]$$

Example : Cylinder with internal pressure P_1 only.

Find the max shear stress.

Solution: Since $P_2 = 0$,

$$\sigma_{rr} = \frac{P_1 a^2}{b^2 - a^2} - \frac{a^2 b^2}{r^2(b^2 - a^2)} P_1$$

$$= \frac{P_1 a^2}{b^2 - a^2} \left(1 - \frac{b^2}{r^2} \right)$$

$$\sigma_{\theta\theta} = \frac{P_1 a^2}{b^2 - a^2} \left(1 + \frac{b^2}{r^2} \right)$$

$$\sigma_{zz} = \frac{P_1 a^2}{b^2 - a^2}$$

$\sigma_{rr}, \sigma_{\theta\theta}, \sigma_{zz}$: the principal stresses ($\sigma_{\theta\theta} > \sigma_{zz} > \sigma_{rr}$)

$$\therefore \tau_{\max}(r) = \frac{\sigma_{\theta\theta} - \sigma_{rr}}{2} = \frac{P_r a^2 b^2}{(b^2 - a^2) r^2}$$

\therefore max shear occurs at the inner surface
where $r = a$

$$\therefore \tau_{\max} = \frac{P_r b^2}{b^2 - a^2}$$

$$\tau_{\max} = \frac{P_r (b/a)^2}{(b/a)^2 - 1}$$

Case study: $b/a = 3$

P_r produces the allowable τ_{\max}

$$\Rightarrow \tau_{\max} = (P_r) \cdot (9/8)$$



To maintain the max shear τ_{\max} under the new internal pressure $1.1 P_r$, the new cylinder should have the ratio b/a :

$$\tau_{\max} = \frac{1.1 P_r (b/a)^2}{(b/a)^2 - 1}$$

$$= (P_r) \cdot (9/8)$$

$$\rightarrow \frac{1.1 (b/a)^2}{(b/a)^2 - 1} = 9/8$$

$$\therefore b/a = 6.7$$



$$I_a \quad b$$

$$\sigma_{\theta\theta} = \frac{P_r a^2 - P_e b^2}{b^2 - a^2} \dots$$

$$\dots + \frac{a^2 b^2}{r^2 (b^2 - a^2)} (P_r - P_e)$$


(5)

$$b \rightarrow \infty \quad (b/a \rightarrow \infty)$$

$$\sigma_{\theta\theta} = -P_2 \quad \text{At the inner surface, } r = a$$

$$\sigma_{\theta\theta} = -P_2 + P_1 - P_2$$

$$\boxed{\sigma_{\theta\theta} = P_1 - 2P_2}$$



$$\text{IF } P_1 = 0, \quad \sigma_{\theta\theta} = -2P_2$$

11.7 Rotating Disc of Constant Thickness

Nov. 29 / 18

Geometry: $t = \text{const.}$, $t \ll b$ (outer radius)

State of Stress: plane stress & axisymmetry

$$\sigma_{zr} = \sigma_{z\theta} = \sigma_{zz} = \sigma_{r\theta} = 0$$

and σ_{rr} and $\sigma_{\theta\theta}$ are functions of r

Equation of Motion:

$$\left\{ \begin{array}{l} \frac{\partial \sigma_{rr}}{\partial r} + \frac{1}{r} \frac{\partial \sigma_{rz}^0}{\partial \theta} + \frac{\partial \sigma_{rz}^0}{\partial z} + \frac{\partial \sigma_{rr} - \sigma_{\theta\theta}}{r} + pr\omega^2 = 0 \\ \frac{\partial \sigma_{rz}^0}{\partial r} + \frac{1}{r} \frac{\partial \sigma_{rz}^0}{\partial \theta} + \frac{2\sigma_{rz}^0}{r} = 0 \\ \Rightarrow d\sigma_{rr}/dr + (\sigma_{rr} - \sigma_{\theta\theta})/r + pr\omega^2 = 0 \end{array} \right.$$

Stress-strain-temperature:

$$\left\{ \begin{array}{l} \sigma_{rr} = \frac{E}{1-\nu^2} (\epsilon_{rr} - \nu \epsilon_{\theta\theta}) - \frac{E\alpha T}{1-\nu} \\ \sigma_{\theta\theta} = \frac{E}{1-\nu^2} (\epsilon_{\theta\theta} - \nu \epsilon_{rr}) - \frac{E\alpha T}{1-\nu} \end{array} \right.$$

Strain-disp:

$$\epsilon_{rr} = \partial u / \partial r = du / dr$$

$$\epsilon_{\theta\theta} = \frac{1}{r} \partial u / \partial \theta + u / r = u / r$$

The solution of the displacement: $u = u(r)$

$$u(r) = \frac{1-\nu^2}{8E} pr\omega^2 r^3 + \frac{\alpha(1+\nu)}{r} \int_r^R r T dr + C_1 r + C_2 / r$$


 C_1 and C_2 are unknown constants.

The Stress

$$\left\{ \begin{array}{l} \sigma_{rr} = \frac{E}{1-\nu^2} \left[\frac{du}{dr} + \nu \frac{u}{r} \right] - \frac{E\alpha T}{1-\nu} \\ \sigma_{\theta\theta} = \frac{E}{1-\nu^2} \left[\nu \frac{du}{dr} + \frac{u}{r} \right] - \frac{E\alpha T}{1-\nu} \end{array} \right.$$

+ temp. change

Case 1: Solid Disk

(w/ const. temperature: $T = \Delta T = 0$)Traction free at $r=b$

Boundary condition:

$$\text{At } r=b, \sigma_{rr} = 0$$

$$\sigma_{px} = \sigma_{xxl} + \sigma_{xym} + \sigma_{xzr}$$

$$\sigma_{py} = \sigma_{xyl} + \sigma_{ygm} + \sigma_{yzr}$$

$$\sigma_{pz} = \sigma_{xzl} + \sigma_{yzm} + \sigma_{zrn}$$

$$\sigma_{pr} = \sigma_{rrl} + \cancel{\sigma_{rwm}} + \cancel{\sigma_{rzr}}$$

$$\sigma_{pa} = \cancel{\sigma_{rl}} + \cancel{\sigma_{wm}} + \cancel{\sigma_{zn}}$$

$$\sigma_{pz} =$$

$$\text{At } r=b, \sigma_{rr} = 0$$

$$\text{At } r=0, |u| < \infty$$

$$C_2 = 0$$

After solving for C_1 , we have:

$$\sigma_{rr} = [(3+\nu)/8] \rho \omega^2 (b^2 - r^2)$$

$$\sigma_{\theta\theta} = [(3+\nu)/8] \rho b^2 \omega^2 - \frac{1+3\nu}{8} \rho \omega^2 r^2$$

The displacement:

$$u(r) = \frac{1}{8E} \rho \omega^2 [(1-\nu)(3+\nu)b^2 r - (1-\nu^2)r^3]$$

The max normal stress occurs at the center of the solid disk:

$$\sigma_{rr, \max} = \sigma_{\theta\theta, \max} = \frac{3+\nu}{8} \rho b^2 \omega^2$$

Case 2: A disk with a hole and $T = 0$

$$\text{At } r=a, \sigma_{rr} = 0$$

$$\text{At } r=b, \sigma_{rr} = 0$$

$$\Rightarrow \sigma_{rr} = \frac{3+\nu}{8} \rho \omega^2 \left[b^2 + a^2 - \frac{a^2 b^2}{r^2} - r^2 \right]$$

$$\sigma_{\theta\theta} = \frac{3+\nu}{8} \rho \omega^2 \left[b^2 + a^2 + \frac{a^2 b^2}{r^2} - \frac{1+3\nu}{3+\nu} r^2 \right]$$

$$(\sigma_{\theta\theta} > \sigma_{rr})$$



The maximum normal stress

$$\text{for } \sigma_{rr}: \frac{d\sigma_{rr}}{dr} = 0$$

$$r = \sqrt{ab} \quad \text{and} \quad \sigma_{rr, \max} = \frac{3+\nu}{8} \rho \omega^2 (b-a)^2$$

For $\bar{J}_{\theta\theta}$:

Max $\bar{J}_{\theta\theta}$ occurs at $r=a$


$$\text{and } \bar{J}_{\theta\theta,\max} = \left(\frac{3+v}{4}\right) \rho w^2 (b^2 + \frac{v}{3+v} a^2)$$

Consider when $a \rightarrow \infty$

$$\bar{J}_{\theta\theta,\max} \rightarrow \left(\frac{3+v}{4}\right) \rho w^2 b^2$$

Special case: $a \xrightarrow{\text{approaches}} b$

$$\bar{J}_{\theta\theta,\max} \rightarrow \rho (bw)^2$$




Example:

$$a = 0.1 \text{ m}$$

$$b = 0.3 \text{ m}$$

$$E = 200 \text{ GPa}$$

$$v = 0.29$$



$$\rho = 7850 \text{ kg/m}^3$$

$$\gamma = 620 \text{ MPa}$$

* max shear stress criterion

The disc is traction free at $r=a$, and $r=b$

$$T=0$$

Find a) the max angular velocity w

b) at the yield velocity, what is the change in thickness in the radial direction.

$$\text{Solution: } \bar{J}_{\max} = \frac{\bar{J}_{\theta\theta,\max}}{2} = \frac{\gamma}{2}$$

$$\Rightarrow \bar{J}_{\theta\theta,\max} = \gamma$$

$$\Rightarrow \frac{3+v}{4} \rho w^2 (b^2 + \frac{1-v}{3+v} a^2) = \gamma$$

$$\Rightarrow w = 1020.77 \text{ rad/s}$$

$$\text{b) Since } u(r) = \frac{\rho w^2}{E} \left[\frac{(1-v)(3+v)}{8} (b^2 + a^2) r + \frac{(1+v)(3+v)}{8} \frac{a^2 b^2}{r} - \frac{v w^2}{8} r^3 \right]$$


$$\text{At } r=a$$

$$u_a = u(a) = \frac{\rho w^2}{E} \cdot a \cdot [(1-v)a^2 + (3+v)b^2]$$

$$= 0.0003100$$

At $r = b$:

$$\begin{aligned} u_b &= u(b) \\ &= \frac{\rho \omega^2}{4E} \cdot b \cdot [(3+v)a^2 + (1-v)b^2] \\ &= 0.0002969 \text{ m} \end{aligned}$$



New inner radius
New outer radius


$$\begin{aligned} a' &= a + u_a \\ b' &= b + u_b \end{aligned}$$

\therefore New thickness in the radial direction

$$\begin{aligned} h' &= b' - a' = (b + u_b) - (a + u_a) \\ &= 0.2 + 0.0002969 - 0.0003100 \\ &= 0.19999999869 \text{ m} \end{aligned}$$

Theory of Elasticity

Stress, Strain



Disp: $u(x,y,z), v(x,y,z), w(x,y,z)$

Stress: $\sigma_{xx}, \sigma_{xy}, \sigma_{xz}, \sigma_{yy}, \sigma_{yz}, \sigma_{zz}$

Strain: $\epsilon_{xx}, \epsilon_{xy}, \epsilon_{xz}, \epsilon_{yy}, \epsilon_{yz}, \epsilon_{zz}$

Strain Disp:

$$\left\{ \begin{array}{l} \epsilon_{xx} = \frac{\partial u}{\partial x} \dots \\ \epsilon_{yy} = \frac{1}{2} \left(\frac{\partial u}{\partial y} + \frac{\partial v}{\partial x} \right) \dots \end{array} \right.$$

Hooke's Law:

$$\epsilon_{xx} = \frac{1}{E} [\sigma_{xx} - \nu (\sigma_{yy} + \sigma_{zz})] \dots$$

$$\epsilon_{xy} = \frac{1}{2G} \sigma_{xy} \dots$$

Equilibrium:

$$\frac{\partial \sigma_{xz}}{\partial x} + \frac{\partial \sigma_{xy}}{\partial y} + \frac{\partial \sigma_{xz}}{\partial z} + bx = 0$$

⋮

Boundary conditions:

$$\partial u / \partial P : u = \bar{u}, v = \bar{v}, w = \bar{w}$$

$$\partial \sigma / \partial P : \sigma_{px} = \bar{f}_x, \sigma_{py} = \bar{f}_y, \sigma_{yz} = \bar{f}_z$$

Compatibility conditions (6)


* Torsion of a general cross-section:

- semi-inverse method

$$u = -\theta y z, \quad v = \theta x z$$

Stress Function $\phi(x,y)$:

$$\left\{ \frac{\partial^2 \phi}{\partial x^2} + \frac{\partial^2 \phi}{\partial y^2} = -2G\theta \right.$$



CROSS-SECTION

$\phi = \text{const along boundary}$

$$* T = 2 \iint_A \phi dA$$

$$\sigma_{xz} = \frac{\partial \phi}{\partial y}$$




$$\sigma_{yz} = -\frac{\partial \phi}{\partial x}$$

* Thick cylinder and rotating disk

* σ_{rr} , $\sigma_{\theta\theta}$, σ_{zz}

* $u(r)$

Mechanics of Materials Method:



$$\iint_A \sigma_{zz} dA = P$$

$$\iint_A \tau_{zx} dA = V_x$$

$$\iint_A \tau_{zy} dA = V_y$$

$$\iint_A y \sigma_{zz} dA = M_x$$

$$\iint_A x \sigma_{zz} dA = M_y$$

$$\iint_A (x \tau_{zy} - y \tau_{zx}) dA = T$$

* Thin-wall member

1° torsion  open
 closed

2° bending