

(1)

OCT. 29TH/18

$$\dot{Q}_{in} + \dot{W}_{shaft,in} + \dot{W}_{pressure, net,in} = \frac{dE_{sys}}{dt}$$

$$e = u + ke + pe = u + \frac{v^2}{2} + gz$$

$$\frac{dE_{sys}}{dt} = \frac{d}{dt} \int_{cv} e\rho dV + \int_{cs} e\rho(\bar{V}_i \cdot \bar{n}) A$$

$$\dot{Q}_{net,in} + \dot{W}_{shaft,in} + \dot{W}_{pressure, net,in} = \frac{d}{dt} \int_{cv} e\rho N + \int_{cs} e\rho(\bar{V}_i \cdot \bar{n}) dA$$

$$\left(\begin{array}{l} \text{The net rate of energy} \\ \text{transfer into a CV by} \\ \text{heat + work transfer} \end{array} \right) = \left(\begin{array}{l} \text{The time rate of} \\ \text{change of the energy} \\ \text{contents of the CV} \end{array} \right) + \left(\begin{array}{l} \text{The net flow rate} \\ \text{of energy out of} \\ \text{the control surface} \\ \text{by mass flow} \end{array} \right)$$

$$\text{Fixed C.V. : } \dot{Q}_{net,in} + \dot{W}_{shaft, net,in} = \frac{d}{dt} \int_{cv} e\rho dV + \int_{cs} (\frac{P}{\rho} + e) \rho(\bar{V}_i \cdot \bar{n}) dA$$

$$\dot{m} = \int_{AC} \rho(\bar{V} \cdot \bar{n}) dA_c$$

$$\dot{Q}_{net,in} + \dot{W}_{shaft, net,in} = \frac{d}{dt} \int_{cv} e\rho dV + \underbrace{\sum_{out} \dot{m} \left(\frac{P}{\rho} + e \right) - \sum_{in} \dot{m} \left(\frac{P}{\rho} + e \right)}_{\text{net energy flux}}$$

heat added to system work added to system

$$\text{where } e = u + ke + pe$$

$$\dot{Q}_{net,in} + \dot{W}_{shaft, net,in} = \frac{d}{dt} \int_{cv} e\rho dV + \sum_{out} \dot{m} \left(\frac{P}{\rho} + u + \frac{v^2}{2} + gz \right) - \sum_{in} \dot{m} \left(\frac{P}{\rho} + u + \frac{v^2}{2} + gz \right)$$

$$\text{where } h = u + Pv$$

$$= u + P/\rho$$

Steady state :

$$\dot{Q}_{net,in} + \dot{W}_{shaft, net,in} = \dot{m} (h_2 - h_1 + \frac{V_2^2 - V_1^2}{2} + g(z_2 - z_1))$$

$$\dot{Q}_{net,in} + \dot{W}_{shaft, net,in} = h_2 - h_1 + \frac{V_2^2 - V_1^2}{2} + g(z_2 - z_1)$$

$$\hookrightarrow h = u + P/\rho$$

$$\dot{W}_{shaft, net,in} + \frac{P_1}{\rho_1} + \frac{V_1^2}{2} + gz_1 = \frac{P_2}{\rho_2} + \frac{V_2^2}{2} + gz_2 + (u_2 - u_1 - \dot{Q}_{net,in})$$

Ideal flow (no mech. energy loss) : $\dot{Q}_{net,in} = u_2 - u_1$ Real flow (w/ mech. energy loss) : $\epsilon_{mech, loss} = u_2 - u_1 - \dot{Q}_{net,in}$

$$\epsilon_{mech,in} = \epsilon_{mech,out} + \epsilon_{mech,loss}$$

(2)

Energy equation in terms of heads

$$\frac{P_1}{\rho_1 g} + \frac{V_1^2}{2g} + Z_1 + h_{\text{pump}, u} = \frac{P_2}{\rho_2 g} + \frac{V_2^2}{2g} + Z_2 + h_L + h_{\text{turbine}, e}$$

$$h_{\text{pump}, u} = \frac{\dot{W}_{\text{pump}, u}}{g} = \frac{\dot{W}_{\text{pump}, u}}{mg} = \frac{R_{\text{pump}} \dot{W}_{\text{pump}}}{mg}$$

$$h_{\text{turbine}, e} = \frac{\dot{W}_{\text{turbine}, e}}{g} = \frac{\dot{W}_{\text{turbine}, e}}{mg} = \frac{\dot{W}_{\text{turbine}}}{R_{\text{turbine}} mg}$$

$$h_L = \frac{E_{\text{mech, loss P:p:ng}}}{g} = \frac{E_{\text{mech, loss P:p:ng}}}{mg}$$


Kinetic energy correction Factor, α

by replacing $V^2/2$ by $\alpha V_{\text{avg}}^2/2$

$$\dot{W}_{\text{in}} + \frac{P_1}{\rho_1} + \alpha \cdot \frac{V_1^2}{2} + gZ_1 = \frac{P_2}{\rho_2} + \alpha_2 \frac{V_2^2}{2} + gZ_2 + \text{losses}$$

Example

Kinetic energy correction factor using actual velocity distribution.



$$\dot{m} = \rho V_{\text{avg}} A, \quad \rho = \text{const.}$$

$$\begin{aligned} K\dot{E}_{\text{act}} &= \int K\dot{e} \delta m = \int_A \frac{1}{2} [V(r)^2] [\rho V(r) dA] \\ &= \gamma_A \rho \int_A [V(r)]^2 dA \end{aligned}$$

$$K\dot{E}_{\text{avg}} = \frac{1}{2} \dot{m} V_{\text{avg}}^2 = \frac{1}{2} \rho A V_{\text{avg}}^3$$

$$\alpha = \frac{K\dot{E}_{\text{act}}}{K\dot{E}_{\text{avg}}} = \frac{1}{A} \int \left(\frac{V(r)}{V_{\text{avg}}} \right)^2 dA$$



Example Pump powered by 15 kW motor, $\eta_{\text{motor}} = 90\%$

$$\dot{V} = 50 \text{ l/s}, D_{in} = D_{out}, Z_1 \cong Z_2$$

$$\eta_{\text{pump}} = \frac{\dot{W}_{\text{pump}, u}}{\dot{W}_{\text{pump}, \text{shaft}}}$$

$$\dot{m} = \rho \dot{V} = (1000 \times 0.050) = 50 \text{ kg/s}$$

$$\dot{W}_u + \dot{m} \left(\frac{P_2}{\rho} + \alpha_2 \frac{V_2^2}{2} + g Z_2 \right) = \dot{m} \left(\frac{P_1}{\rho} + \alpha_1 \frac{V_1^2}{2} + g Z_1 \right)$$

$$\dot{W}_u = \dot{m} \left(\frac{P_2 - P_1}{\rho} + \alpha_2 \frac{V_2^2}{2} - \alpha_1 \frac{V_1^2}{2} + g(Z_2 - Z_1) \right)$$


$$A_1 V_1 = A_2 V_2$$

$$A_1 = A_2 \rightarrow V_1 = V_2$$

$$\dot{W}_u = \dot{m} \left(\frac{P_2 - P_1}{\rho} \right) = 50 \left(\frac{300 - 100}{1000} \right) = 10 \text{ kW}$$

$$\dot{W}_{\text{shaft}} = \eta_{\text{motor}} \times \dot{W}_{\text{motor}} = (0.9)(15) = 13.5 \text{ kW}$$

$$\eta_{\text{pump}} = \frac{10}{13.5} = 0.741 \text{ or } 74.1\%$$



$$\dot{E}_{\text{loss}} = \dot{m} C \Delta T \rightarrow \Delta T = \frac{\dot{E}_{\text{loss}}}{\dot{m} C}$$

$$\Delta T = \frac{(3.5)}{(50)(4.18)} = 0.017^\circ\text{C}$$

→ 6.13

Example:

$$\dot{V} = 100 \text{ m}^3/\text{s}, \quad Z_1 = 120 \text{ m}, \quad P_1 = P_2, \quad V_1 \approx V_2 \approx 0$$

$$\frac{P_1}{\rho g} + \frac{\alpha V_1^2}{2g} + Z_1 + h_{\text{comp}} - h_{\text{turb}} - h_{\text{loss}} = \frac{P_2}{\rho g} + \frac{\alpha V_2^2}{2g} + Z_2$$

$$Z_1 - h_{\text{turb}} - h_{\text{loss}} = 0$$

$$\Rightarrow h_{\text{turb}} = Z_1 - h_L$$

$$= 120 - 35 = 85 \text{ m}$$

$$\dot{W}_{\text{turb, ideal}} = \dot{m} h_{\text{turb}} = \rho \dot{V} g h_{\text{turb}} = (1000)(100)(9.81)(85)$$

$$\dot{W}_{\text{turb, ideal}} = 83400 \text{ kW}$$

$$\dot{W}_{\text{turb, out}} = \eta_{\text{turb gen}} \dot{W}_{\text{turb, ideal}} = (0.8)(83400) = 667 \text{ MW}$$

(1)

Oct. 31/18

Example

"A fan is to be selected to cool a computer case..."

$$\dot{m} \left(\frac{P_3}{\rho} + \alpha_3 \frac{V_3^2}{2} + gZ_3 \right) + \dot{W}_{fan} = \dot{m} \left(\frac{P_4}{\rho} + \alpha_4 \frac{V_4^2}{2} + gZ_4 \right) + \dot{E}_{losses}$$

$$\dot{m} = \rho V$$

$$V_{case} = (12 \times 40 \times 40)(0.5) = 9600 \text{ cm}^3$$

$$\dot{V} = 9600 / 1s = 9600 \text{ cm}^3/s$$

$$= 9.6 \times 10^{-3} \text{ m}^3/s$$

$$\dot{m} = (1.2)(9.6 \times 10^{-3}) = 0.0115 \text{ kg/s}$$

$$\dot{W}_{fan,u} = \dot{W}_{fan} - \dot{E}_{loss} = \dot{m} \alpha_2 \frac{V^2}{2}$$

For Fully developed turbulent flow $\alpha_2 = 1.11$

$$\dot{W}_{fan,u} = 0.0115(1.11) \frac{V^2}{2} \Rightarrow \dot{W}_{fan,u} = 0.153 \text{ W}$$

$$A = (\pi/4)D^2 = \frac{\pi(0.05)^2}{4} = 1.96 \times 10^{-3} \text{ m}^2$$

$$V_2 = \dot{V}/A = \frac{9.6 \times 10^{-3}}{1.96 \times 10^{-3}} = 4.9 \text{ m/s}$$

$$\eta_{th} = \frac{\dot{W}_{fan,u}}{\dot{W}_{electricity}} = \dot{W}_{electricity} = \frac{\dot{W}_{fan,u}}{\eta_{th}} = \frac{0.153}{0.3}$$

$$\rightarrow \dot{W}_{electricity} = \boxed{0.506 \text{ W}}$$

b) $\dot{m} \left(\frac{P_3}{\rho} + \alpha_3 \frac{V_3^2}{2} + gZ_3 \right) + \dot{W}_{fan} = \dot{m} \left(\frac{P_4}{\rho} + \alpha_4 \frac{V_4^2}{2} + gZ_4 \right) + \dot{E}_{loss}$

$$\dot{W}_{fan,u} = \dot{W}_{fan} - \dot{E}_{loss} = 0.153 \text{ W}$$

Assuming $V_3 A_3 = V_4 A_4$

$$V_3 = V_4$$

$$\alpha_3 = \alpha_4$$

$$\dot{W}_{fan,u} = \dot{m} \frac{P_4 - P_3}{\rho} \Rightarrow P_4 - P_3 = \frac{\rho \dot{W}_{fan,u}}{\dot{m}}$$

$$P_4 - P_3 = \frac{(1.2)(0.153)}{(0.0115)} = \boxed{15.8 \text{ Pa}}$$

Linear momentum:

$$\vec{F} = m\vec{a} = m \frac{d\vec{V}}{dt} = \frac{d(m\vec{V})}{dt}$$

Angular momentum:

$$\vec{M} = I\vec{\alpha} = I \frac{d\vec{\omega}}{dt} = \frac{d(I\vec{\omega})}{dt} = \frac{d\vec{H}}{dt}$$

about X-axis:

$$M_x = I_x \frac{d\omega_x}{dt} = \frac{dH_x}{dt}$$

→ Total angular momentum of a rotating body remains constant when the net torque acting on it is zero.

Thus, angular momentum is conserved.

Body Forces: gravity, electric, magnetic

Surface Forces: that act on the control surface
(such as pressure and viscous forces
and reaction forces at points of contact)

→ only external forces are considered in analysis

Total Force acting on control volume: $\sum \vec{F} = \sum_{body} \vec{F} + \sum_{surface} \vec{F}$

Normal stresses: pressure and viscous stresses

Shear stresses: composed entirely of viscous stresses

Surface force acting on a differential surface element:

$$d\vec{F}_{surface} = T_y \cdot \vec{n} dA$$

General: $\sum \vec{F} = \frac{d}{dt} \int_{cv} \rho \vec{V} dV + \int_{cs} \rho \vec{V} (\vec{V} \cdot \vec{n}) dA$

$$\left(\begin{array}{l} \text{The sum of} \\ \text{all forces acting} \\ \text{on CV} \end{array} \right) = \left(\begin{array}{l} \text{the time rate of} \\ \text{change of lin. mom.} \\ \text{of the contents of CV} \end{array} \right) + \left(\begin{array}{l} \text{Net flow rate} \\ \text{of linear mom.} \\ \text{out of the CS} \\ \text{by mass flow} \end{array} \right)$$