

Example 4: A ball bearing is to operate on the following work cycle

Radial load of 1400 lb at 200 rpm for 25% of the time
 " " 2000 lb at 500 rpm for 20% "
 " " 800 lb at 400 rpm for 55% "

The inner ring rotates; loads are steady. Find the minimum value of the basic rating load C , for a suitable bearing for this application if the required life is 7 years at 4 hrs per day.

Solution:

On the basis of a work cycle of 1 min., we have:

Load lb.	Assumed interval 1m:n	rpm	In assumed interval, rev.
$P_1 = 1400$	0.25	200	50
$P_2 = 2000$	0.20	500	100
$P_3 = 800$	<u>0.55</u>	400	<u>220</u>
TOTAL :	1		370

$$\text{Then } \alpha_1 = \frac{50}{370} ; \quad \alpha_2 = \frac{100}{370} ; \quad \alpha_3 = \frac{220}{370}$$

Assuming 250 working days in a year

$$N_c = 7 \times 250 \times 4 \times 60 \times 370 = 155,400,000$$

$$\frac{10^6 C^3}{N_c} = \frac{50}{370} \times 1400^3 + \frac{100}{370} \times 2000^3 + \frac{220}{370} \times 800^3$$

$$= 2,837,400,000$$

$$\text{or } C^3 = 2,837,400,000 N_c = 440,930,000,000$$

$$C = 7,610 \text{ lb}$$

TABLE 9.1:

∴ bearing No. 308 should be satisfactory with 90% prob. of surviving 7 years.

5 - Design For Different Confidence Levels

When a degree of reliability greater than 90% is required, the expected life will be reduced as

Follows :

$$L_n = \alpha_i L_{10}$$

Where α_i is Found from Table 9-4 (spotts)

→ see Assignment 10


Spur Gears

1 - Characteristics :

- the drive is positive, and with circular gears, the angular velocity ratio is constant
- the center distances may be relatively short, thus making a compact drive
- Provision may be made for shifting gears, and in some cases for interchanging them to change the speed of the driven members
- the efficiency is high, since the loss of power may be 1 percent or less of the power transmitted
- the maintenance of the drive is inexpensive and the life is long.

2 - Spur gear terminology

- Pitch Surfaces : The pitch surface is the surface of the rolling cylinder that the gear may be considered to replace



Pitch circle : the pitch circle is a right section of the pitch surface

Addendum circle : the addendum circle is the circle bounding the ends of the track

Dedendum circle : the dedendum circle is the circle bounding the bottom of the spaces between the teeth

Addendum : the addendum is the radial distance between the addendum circle and the pitch circle.

Dedendum : the dedendum is the radial distance between the pitch circle and the dedendum circle


Clearance : the difference between the dedendum of one gear and the addendum of the mating gear

Backlash : the difference between the tooth space of one gear and the tooth thickness of the mating gear measured on the pitch circle

Circular pitch : circular pitch is the distance from a point on one tooth to the corresponding point on the adjacent tooth measured on the pitch circle. Its symbol, p ; the units are inches.

Diametral pitch: diametral pitch is the number of teeth on a gear per inch of its pitch diameter. its symbol is P .

3 - Strength of Gear Teeth (Lewis Equation)



(Forces on Gear Teeth)

Lewis assumed the tooth to be a cantilever beam of parabolic profile, and therefore, it has uniform strength at all cross-sections. Since the tooth is stronger than the assumed beam except at TC, this is considered the critical section where he found:

$$Wh = \frac{SFT^2}{6} \quad \text{or} \quad W = \frac{SFT^2}{6h}$$

Introducing the circular pitch P

$$W = \frac{SFT^2}{6h} \times \frac{P}{P} = SFPy$$

where $y = \frac{t^2}{6hP} = \text{Form Factor (Table 18-1, H.O.)}$

To approximate the effect of dynamic loading the allowable stress is given by:

$$S_{all} = S_0 C_v$$

Where, S_{all} = allowable stress, psi

S_0 = basic stress, psi (From table 18-2, H.O.)

$C_v = \frac{600}{(600+v)} = \underbrace{\text{Velocity Factor}}_{\text{for Spur gears}} \text{ (Table 18-4, H.O.)}$

v = pitch-line velocity (fpm)

(For all values in 18-1
H.O.)

The induced stress is :

$$W = SF\gamma y$$

$$\text{or } S_{\text{ind}} = \frac{W}{F\gamma y}$$

Let T = transmitted torque, lb-in

D = pitch diameter, in

n = number of teeth

P = diametral pitch = n/D

$K = F/P = 3 \text{ to } 4$ (normal service)

$$\text{Then; } S_{\text{ind}} = \frac{W}{F\gamma y} = \frac{WP^2}{E_p P^2 P^2 y} = \frac{WP^2}{K\pi c^2 y} \quad \left. \begin{array}{l} \{ PP = \frac{Pn}{D} \\ = \pi \end{array} \right.$$

$$\text{but } W = 2T/D = 2TP/n$$

$$\text{and } S_{\text{ind}} = \frac{2TP^3}{K\pi c^2 ny}$$

Based on experience it is found that for good proportions the following relation must hold.

$$\hookrightarrow \text{must hold; } 3P \leq F \leq 4P$$

$$\text{or broadly; } 2P \leq F \leq 5P$$

Example 1 → It is required to determine the proportions of a spur gear drive to transmit 100 hp from a shaft rotating at 1170 rpm to a low-speed shaft with a speed reduction of 3:1. Assume that the teeth are a 20° full-depth system, with 24 teeth on the pinion. The pinion is to be SAE-1045 and the gear SAE-1030 steel. Assume that the torque at starting is 130% of torque at rating.

Solution: